



DOCKET: CU-1516

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Terumi Sunaga )

SERIAL NO: 08/820,608 )

) Group Art Unit: 2661

FILED: March 19, 1997 )

) Examiner: K.Vanderpuye

TITLE: Spread Spectrum Communication Transmitter and Receiver and  
CDMA Mobile Communication System and Method

THE ASSISTANT COMMISSIONER FOR PATENTS  
Washington, D.C. 20231

CLEAN VERSION OF CLAIMS 18-20

RECEIVED  
SEP 21 2001  
Technology Center 2600

~~18.~~ A transmitter used in a CDMA mobile communication system comprising:

a pilot transmit unit further comprising:

a pilot data generator which generates pilot data;

a first modulator which modulates the pilot data;

a second modulator which spreads a spectrum of modulated pilot data

from the first modulator to thereby generate a pilot signal; and

a timing generator which generates a timing signal applied to at least one of

the pilot data generators and the first and second modulators so that

the pilot signal is intermittently transmitted; and

traffic channel transmit units which respectively transmit data signals in

respect of traffic channels.

~~19.~~ A transmitter used in a CDMA mobile communication system as claimed in  
claim ~~18~~, wherein said pilot signal has a period shorter than an interval in which the pilot  
signal is intermittently transmitted.

~~20.~~ A receiver used in a CDMA mobile communication system comprising:

25

G

*Pl* a pilot channel receive unit which demodulates pilot signals respectively transmitted intermittently in a spread spectrum formation by transmitters, and detects from the pilot signals, a timing for a traffic channel demodulation; and

a traffic channel receive unit which demodulates data at the timing detected by said pilot channel receive unit; and the timing detected by comparing peaks of the pilot signals intermittently transmitted, the timing for the traffic channel demodulation corresponding to a greatest one of the peaks.

---